

WTS WATER TREATMENT

Universal treatment tanks with interchangeable coalescing media to suit all applications

Ideal solution when dewatering and dealing with stubborn suspended solids. The coalescing/lamella media provides a huge settling area and encourages settlement of all types of silt. Silt and Sludge is collected in the hopper and can be easily removed via the dump valve. Systems can be used with or without Flocculant. Media can be provided with varying diameter openings making the WTS the perfect system for any application. System can also be fitted with remote water quality monitoring systems and/or auto desludging pumps.

Lamella Coalescing media, can be used with Flocculant

Oil Skimmer & optional Hydrocarbon filter pads

Simple to set up, simple to empty, simple to operate

Solids emptied via dump valve for easy cleaning

AVAILABLE FOR HIRE OR PURCHASE

Dims(mm)/ Weight approx.	WTS 2880 (L) 1560 (W) 1510(H) / 820kg WTS XL 4020 (L) 1830 (W) 2140 (H) / 1320kg WTS XXL 4940 (L) 2370 (W) 2260 (H) / 2200kg WTS XXL LH 4210 (L) 2210 (W) 3250 (H) / 3200kg
Optimum Max Flowrate	WTS 15m ³ /hr WTS XL 25m ³ /hr WTS XXL 30-40m ³ /hr WTS XXL LH 50-60m ³ /hr
Power Required	NOT REQUIRED* *110V required if dosing or remote monitoring
Consumables	Flocculant Block (optional) Hydrocarbon Filter Pads (optional)

For further information contact Lohan Environmental :
info@lohanenvironmental.ie

